

# FLAT-PROOF TIRE & WHEEL ASSEMBLIES

- No More Flats - No More Downtime - More Happy Customers -



Walkbehinds



Zero Turns



Velkes



Jungle Jim



Wheelbarrows



Finishing Mowers

## Brand Fitments:



Part #	Tire Size	Weight	Description
206CM	8X300-4 SMOOTH	5.7 lbs.	Mounted on a 4X2.25" steel wheel painted white with 3.25" centered hub length and 3/4" roller bearings. <b>Replaces OEM:</b> Land Pride <b>**CARLISLE RELIANCE TIRE**</b>
107CM	8X300-4 SMOOTH	5.6 lbs.	Mounted on a 4X2.25" steel wheel painted white with 3.5" centered hub length and 5/8" roller bearings. <b>Replaces OEM:</b> Walker, Swisher <b>**CARLISLE RELIANCE TIRE**</b>
208CM	9X350-4 SMOOTH	7.7 lbs.	Mounted on a flat base 4X2.25" steel wheel painted white with 3.25" centered hub length and 5/8" roller bearings. <b>Replaces OEM:</b> * Grasshopper <b>**CARLISLE RELIANCE TIRE**</b>
211CM	9X350-4 SMOOTH	7.1 lbs.	Mounted on a flat base 4X2.25" steel wheel painted white with 3.25" centered hub length and 3/4" roller bearings. <b>Replaces OEM:</b> Gravely, Ariens, Kubota <b>**CARLISLE RELIANCE TIRE**</b>
212CM	9X350-4 SMOOTH	6.7 lbs.	Mounted on a flat base 4X2.25" steel wheel painted white with 3.50" centered hub length and 3/4" sintered iron bushings. <b>Replaces OEM:</b> King Kutter <b>**CARLISLE RELIANCE TIRE**</b>
209CM	9X350-4 SMOOTH	7.7 lbs.	Mounted on a flat base 4X2.25" steel wheel painted white with 4.0" centered hub length and 5/8" roller bearings. <b>Replaces OEM:</b> Scag, Ransomes <b>**CARLISLE RELIANCE TIRE**</b>
210CM	9X350-4 SMOOTH	7.4 lbs.	Mounted on a flat base 4X2.25" steel wheel painted white with 4.5" centered hub length and 3/4" roller bearings. <b>Replaces OEM:</b> Exmark, JDeere, Toro <b>**CARLISLE RELIANCE TIRE**</b>
145LS FILLED	9X350X4 T/SAVER	xx lbs.	Mounted on a zinc plated steel bolted wheel with 3.75" centered hub length and 3/4" roller bearings. <b>Replaces OEM:</b> Single Velke <b>** FOAM FILLED TIRE**</b>

# FLAT-PROOF TIRE & WHEEL ASSEMBLIES

Part #	Tire Size	Weight	Description
535LS FILLED	410X4 T/SAVER	xx lbs.	Mounted on a zinc plated steel bolted wheel with 2.19" off-centered hub length and 1" roller bearings.  <b>Replaces OEM: Jungle Wheel      ** FOAM FILLED TIRE**</b>
231CM	11X400-5  SMOOTH	9.7 lbs.	Mounted on a 5X3.25" steel wheel painted white with 5" centered hub length and 3/4" angular contact heavy duty ball bearings. <b>Replaces OEM: Ariens, Jdeere, Dixon      **CARLISLE RELIANCE TIRE**</b>
223CM	13X500-6  SMOOTH	13.1 lbs.	Mounted on a 6X3.25" steel wheel painted silver with 3.75" centered hub length and 5/8" double grooved, sealed heavy duty ball bearings. <b>Replaces OEM: Dixie Chopper      **CARLISLE RELIANCE TIRE**</b>
221REL	13X500-6	13.7 lbs.	Mounted on a 6X3.25" steel wheel painted white with 5.625" centered hub length and 3/4" cups pressed for tapered roller bearings. ** Comes with uninstalled 3/4" tapered bearings, seals and spacers. <b>Exmark, Toro, Scag, Wright, Ferris      **CARLISLE RELIANCE TIRE**</b>
246CM	13X650-6  RIB	15.5 lbs.	Mounted on a 6X4.5" steel wheel painted silver with 3.75" centered hub length and 5/8" double grooved, sealed heavy duty ball bearings. <b>Replaces OEM: Dixie Chopper      **CARLISLE RELIANCE TIRE**</b>
245CM	13X650-6  SMOOTH	16.9 lbs.	Mounted on a 6X4.5" steel wheel painted white with 7.25" centered hub length and 3/4" cups pressed for tapered roller bearings. ** Comes with uninstalled 3/4" tapered bearings, seals and spacers. <b>Replaces OEM: Exmark, Toro, Scag      **CARLISLE RELIANCE TIRE**</b>
247CM	15X600-6  RIB	19.4 lbs.	Mounted on a 6X4.5" steel wheel painted silver with 3.75" centered hub length and 5/8" heavy duty ball bearings. <b>Replaces OEM: Dixie Chopper      **CARLISLE RELIANCE TIRE**</b>
30-43790			<b>bearing kit for 221REL &amp; 245CM      2 TAPERED 2 CAPS &amp; 2 BEARINGS SPACERS</b>

\*\* Tapered bearing cones, seals, and spacers: These will be sent uninstalled. For proper installation, loading must occur at point of use.

## More Flat Free Polyurethane Tire & wheel Assemblies:

00001M	480X8	8 lbs	480X8 MARATHON FLAT-FREE <b>RIBBED</b> WHEELBARROW TIRES. TIRES ARE MOUNTED ON A WHITE STEEL WHEEL WITH 6" CENTERED HUB LENGTH AND 5/8" BALL BEARINGS
00030M	480X8	8 lbs	480X8 MARATHON FLAT-FREE <b>SMOOTH</b> ROOFING TIRES. TIRES ARE MOUNTED ON A WHITE STEEL WHEEL WITH 6" CENTERED HUB LENGTH AND 1" BUSHINGS.
00047M	480X8	8 lbs	480X8 MARATHON FLAT-FREE <b>KNOBBY</b> WHEELBARROW TIRES. TIRES ARE MOUNTED ON A WHITE STEEL WHEEL WITH 6" CENTERED HUB LENGTH AND 5/8" BALL BEARINGS.
00063M	480X8	8 lbs.	480X8 MARATHON FLAT-FREE <b>RIBBED</b> WHEELBARROW TIRES. TIRES ARE MOUNTED ON A WHITE STEEL WHEEL WITH 3" CENTERED HUB LENGTH AND 3/4" BALL BEARINGS.
00003M	350X8	6 lbs.	350X8 MARATHON FLAT-FREE <b>RIBBED</b> WHEELBARROW TIRES. TIRES ARE MOUNTED ON A WHITE STEEL WHEEL WITH 6" CENTERED HUB LENGTH AND 5/8" BALL BEARINGS.
00010M	410X4	4 lbs.	410X4 MARATHON FLAT-FREE <b>SAWTOOTH</b> TIRES. TIRES ARE MOUNTED ON A SILVER STEEL WHEEL WITH 2.25" OFF CENTERED HUB LENGTH AND 5/8" BALL BEARINGS.
00011M	410X4	4 lbs.	410X4 MARATHON FLAT-FREE <b>SAWTOOTH</b> TIRES. TIRES ARE MOUNTED ON A SILVER STEEL WHEEL WITH 2.25" OFF CENTERED HUB LENGTH AND 3/4" BALL BEARINGS.
00026M	280X4	3 lbs.	280X4 MARATHON FLAT-FREE <b>JAG</b> TIRES. TIRES ARE MOUNTED ON A SILVER STEEL WHEEL WITH 3" CENTERED HUB LENGTH AND 1/2" BALL BEARINGS.
01100M	18X850X8	28 lbs.	18X850X8 MARATHON FLAT-FREE <b>RIBBED</b> ROOFING TIRES. TIRES ARE MOUNTED ON A SILVER STEEL WHEEL WITH 3.25" CENTERED HUB LENGTH AND 1" ROLLER BEARINGS.
45004M	sealant	16 oz.	FLAT FREE TIRE SEALANT - 16 oz
45007M	sealant	32 oz.	FLAT FREE TIRE SEALANT - 32 oz





