



2015 Tubes & Valves Stems



CARLISLE



Firestone.

Ken Jones Inc.
P.O. Box 782
73 Chandler Street
Worcester, MA 01613
Call: 1-800-225-9513
Fax: 1-508-755-4397
www.kenjones.com
sales@kenjones.com

Tire Tubes for Snow Blowers, Tractors, ATVs, UTVs, Skid Steers, Forklifts, Backhoes. Graders, Loaders, Forestry Skidders, Trucks and Cars..

About Ken Jones Tires...

Welcome to Ken Jones Tires and the Jones family. A quick background ...Ken Jones Tires is not a new company. We are a third generation family business that started way back in 1938 by Ken Jones. Over the past 75 plus years we have evolved from a



local retail tire dealer to a leading niche player in specialty tires, tubes and tire chains market.

We are an authorized distributor for both Carlisle and Firestone tubes.. We sell tire tubes to customers all over the country and have a vast dealer network as well as partner warehouse shipping points strategically located across the United States.

Ken Jones Tires is not new to the internet. We started our first website, www.kenjones.com, in the early 90's. In 2009 completed a major ecommerce upgrade including live inventory, live pricing, thousands of pictures and video. We also launched our blog, www.kenjonestiresblog.com. There you will find many helpful articles as well as "tips of the trade". Check it out.

Expert Authority

I guess you could call us the "Gurus" in specialty tires and tubes. That's what we do ten hours a day every day. We've heard every question, every unusual application, every day, you name it. And we will take the extra step and search the US for your hard to find tire tubes. Our customer service experts average 28 years experience in these markets. **We sell to thousands of tire dealers, equipment companies, golf courses as well as the general public.**

Trusted Advisor

Unlike websites that don't want you to call, **we encourage you to call us**. Our toll free number is posted in large print on all search and shopping cart pages. Specialty tires and tubes can be confusing and a quick phone call can point you in the right direction.

Don't forget to call us if needed at 1-800-225-9513. We will be happy to assist you.

2 Tire Tubes for Snow Blowers, Tractors, ATVs, UTVs, Skid Steers, Forklifts, Backhoes. Graders, Loaders, Forestry Skidders, Trucks and Cars..

TUBES

Passenger Car Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
RADIAL				
DR 12 400/530X12		TR13	10	323844
ER12/13 P145/155/80R12/13	6X12	TR13	10	322160
FR13/14 P165/80R13/14, P175/185/70R13/14	6/7X14	TR13	10	322010
FR 15 P155/165R15, P185/205/50/60/65R15	500/600X15	TR13	10	322170
GR13/14/15 P185R14/15, P185/205/70/80R13,14,15	24/25X850X14, 25X750X15	TR13	10	322020
KR14/15 P215/225/70R14/15, P205/215/75R15	670/825X14/15	TR13	10	322030
MR14/15 P235/255/70R14/15, P225/235/85R14/15	760/900X14/15	TR13	10	322040
GR/KR16 P215/65R16, P205/235/60R16	550/650X16, 7/8X16	TR13	10	322050

Light Truck Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
RADIAL				
31/1050/1150R15.9/10/11R15LT	31X1050/1150X15	TR13R	6	322310
35X1250R15LT, LT265/315/60/70R15/17, 12R15/16LT		TR13R	6	552038
750R16, LT215/235/80R16		TR150	10	322060
750R16, LT225/245/70/85R16, LT225/265/60/70R17, P245/265/60/70R16/17		TR13R	10	322200
750R16, LT215/235/85R16, LT225/255/70R16		TR15CW	10	322220
750R16		TR440	10	322210
900R15/16		TR150	4	554516
950/10R16.5		TR15	6	322320
10/12R16.5, 31x105R16.5, 33X1250R16.5, 265/305/70/80R16.5		TR15CW	6	552399
750R17/18		TR440	10	553003
8/9R19.5, 225/70R19.5		TR15CW	6	556641

Low Platform Trailer Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
RADIAL & BIAS				
7/8/9X14.5LT		TR300	6	322290
7/8/9R14.5LT		TR15CW	10	551988
700/750R15 TR		TR440	6	322450
825R15 TR		TR444	6	322240
900/1000/1100R15 TR		TR444	6	322250



TR13 Passenger, light truck, front tractor, industrial, L&G sizes. Valve is straight, rubber covered, 1.38" long. Maximum inflation is 60 psi. Rim hole 0.453". Not intended for use with liquid ballast. Not bendable. B6 bushing allows use in a 0.625" rim hole.



TR150 Light truck, front tractor sizes. Valve is rubber covered and is 3.5" long. Supplied straight but is hand bendable. Rim hole 0.625". Maximum inflation 100 psi. Not intended for use with liquid ballast.



TR15CW Front tractor, L&G sizes. Valve is straight, rubber covered, 1.38" long. Maximum inflation is 60 psi. Rim hole 0.625". Not intended for use with liquid ballast. Not bendable.



TR440 Light truck, truck-bus, mining sizes. Supplied bent. Bent length is 3.0 to 5.7 inches. Maximum inflation is 150 psi. Rim should be slotted. Not intended for use with liquid ballast.



TR300 Limited truck-bus sizes. Valve is 1.97" long. Not bendable. Maximum inflation 150 psi. Not intended for use with liquid ballast. Can be replaced by TR15CW for most applications.

TUBES

Medium and Heavy Truck Tubes


Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
RADIAL & BIAS				
750R20		TR441	6	553020
825R20		TR442	4	322080
900R20		TR443	4	322090
1000R20	12/80R20	TR444	4	322100
1100R20	13/80R20	TR444	4	322110
1200R20	14/80R20	TR444	4	322460
1300/1400R20		TR445	2	553105
1000R22		TR444	2	322270
1100R22		TR444	4	322280
1100/1200R24/25		TR444	2	553173
1300/1400R24	1400R25	TR445	2	553190
11/12R22.5	275/80R22.5, 295/75R22.5	TR300	4	556726
11/12R24.5	285/75R24.5	TR15CW	4	556760

Skid Steer, Loader / Grader Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
RADIAL & BIAS				
27X850/1050X15	215/70D15, 260/65D15	TR15CW	10	551813
27X850/1050X15	215/70D15, 260/65D15	TR218A	6	251055
10X16.5	265/70D16.5	TR15CW	6	322480
12X16.5	305/70D16.5	TR15CW	6	322490
10/12R16.5	265/70D16.5, 305/70D16.5	TR15CW	6	552399
12R16.5	305/70D16.5	TR218A	6	100465
14R17.5	355/70R17.5, 33X1550X16.5	TR15CW	4	556624
14R17.5	355/70R17.5, 33X1550X16.5	TR218A	4	100474
15/18R19.5, 355/80D20	355/445/65R19.5, 44X1800X20	TR218A	2	556675
1300/1400R24		TR220A	1	322341
15.5/17.5R25	1600R24/25	SP1000	1	540846
15.5/17.5R25	1600R24/25	TR220A	1	540765
17.5R25		TRJ1175C	1	323661
20.5R25	1800R25	SP1000	1	540854



Rear tractor, front tractor, flotation, forestry, L&G and drag racing sizes.
TR218 Valve is 0.81" long and is designed to lock into rim hole using LN10 rim nut (supplied). Not bendable. Rim hole 0.625. Maximum inflation 150 psi. Made for liquid ballast.



Grader, off highway, and flotation sizes. Extension must be applied. Made for rim hole 0.818" or slot. Maximum inflation 150 psi. Made for use with liquid ballast.
SP1000



Front tractor, L&G sizes. Valve is straight, rubber covered, 1.38" long. Maximum inflation is 60 psi. Rim hole 0.625". Not intended for use with liquid ballast. Not bendable.
TR15CW



Light truck, truck-bus, mining sizes. Supplied bent. Bent length is 3.0 to 5.7 inches. Maximum inflation is 150 psi. Rim should be slotted. Not intended for use with liquid ballast.
TR440



Limited truck-bus sizes. Valve is 1.97" long. Not bendable. Maximum inflation 150 psi. Not intended for use with liquid ballast. Can be replaced by TR15CW for most applications.
TR300

TUBES

Front Farm / Implement Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
400X9		TR13	12	TWE31
900/9.5LX10		TR150	4	538981
400/480X12	530X12, 5X12	TR13	10	320901
23X850/1050X12, 23X950X12, 24X850X12		TR13	10	321370
26X1200X12, 24X1300X12, 24X1200X12, 10.0/80X12		TR13	10	321050
6X12, 7X12		TR13	10	322160
6X14, 7X14		TR13	10	322010
25X850X14, 24X850X14		TR13	10	322020
9.5LX14, 9.5LX15, 11LX14		TR13	6	322390
400/500X15	590X15	TR13	6	322350
25X750X15		TR13	10	322020
670X15, 212/80D15	7.5L/760X15	TR13	10	322030
27X850X15, 27X950/1050X15		TR13	10	551813
27X850X15, 27X950/1050X15		TR218A	6	251055
29/31/33X1200/1250/1350X15		TR15CW	6	322400
29/31/33X1200/1250/1350X15		TR218A	6	322150
11LX15/16	29/31/33X1200/1250/1350X15	TR15CW	6	322400
11LX15/16	29/31/33X1200/1250/1350X15	TR218A	6	322150
12.5LX15/16, 31X1550X15		TR15CW	6	323810
12.5LX15/16, 31X1550X15		TR218A	6	322470
550/600X16		TR15	6	322120
650/750X16		TR15	6	322360
1000X16, 1000X15		TR15CW	6	322130
1100X16		TR15CW	6	322370
13.6X16, 14LX16.1		TR218A	7	320032
13.6R16		TR218A	4	552833
16.5LX16.1	18.4X16.1, 19LX16.1	TR218A	4	320033
21.5LX16.1		TR218A	2	320034
750X18	650X18	TR15	6	322140
400X19	400X18	TR15	6	322380
750/825X20		TR15	6	552488
900/1000X20		TR15CW	4	552496
44X1800X20, 41X1400X20	355/80D20, 15/18R19.5	TR218A	2	556675



TR13 Passenger, light truck, front tractor, industrial, L&G sizes. Valve is straight, rubber covered, 1.38" long. Maximum inflation is 60 psi. Rim hole 0.453". Not intended for use with liquid ballast. Not bendable. B6 bushing allows use in a 0.625" rim hole.



TR150 Light truck, front tractor sizes. Valve is rubber covered and is 3.5" long. supplied straight but is hand bendable. Rim hole 0.625". Maximum inflation 100 psi. Not intended for use with liquid ballast.



TR15CW Front tractor, L&G sizes. Valve is straight, rubber covered, 1.38" long. Maximum inflation is 60 psi. Rim hole 0.625". Not intended for use with liquid ballast. Not bendable.



TR218 Rear tractor, front tractor, flotation, forestry, L&G and drag racing sizes. Valve is 0.81" long and is designed to lock into rim hole using LN10 rim nut (supplied). Not bendable. Rim hole 0.625. Maximum inflation 150 psi. Made for liquid ballast.

TUBES

Rear Tractor Tire Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
RADIAL & BIAS				
600/7X16		TR218A	10	551244
750/8/9.5X16		TR218A	10	551236
12.4/13.6R16	14LR16.1, 36X1350R15, 14.5/75R16.1	TR15CW	4	552453
13.6X16		TR218A	7	320032
13.6R16		TR218A	4	552833
18.4X16.1	16.5X16.1, 19.5IX16.1	TR218A	4	320033
21LX16.1		TR218A	2	320034
750/8X18		TR15CW	4	532118
8.3/9.5X18/20		TR218A	10	551309
8.3/9.5/10.5X18/20	10.5/12.5R18/20	TR15CW	6	322000
9.5R18/20	10.5/12.5R18/20	TR15CW	6	281926
15/18R19.5, 41X1400X20	44X1800X20, 355/80D20	TR218A	2	556675
8.3/9.5R22		TR218A	4	552850
8.3/9.5R24	750R24	TR218A	8	323601
11.2/12.4R24	320/85R24	TR218A	4	323960
13.6/14.9R24	340/380/85R24	TR218A	3	323950
14.9/16.9/17.5LR24	460/70R24	TR218A	3	323760
18.4/19.5L/21LR24	500/540/70R24	TR218A	2	323770
13.6/14.9R26		TR218A	3	324110
23.1/28LRX26		TR218A	1	550892
11.2/12.4R28		TR218A	3	323591
13.6/14.9R28	14.9R30, 340/380/85R28/30	TR218A	3	323750
16.9/18.4R28/26	480/80R26, 420/85R28	TR218A	2	323730
6/7.2X30		TR218A	1	312136
16.9/18.4R30	420/90R30, 480/80R30	TR218A	2	323780
9.5R32		TR218A	4	552901
11.2/12.4R34/36		TR218A	3	323651
16.9/18.4R34	420/480/85R34	TR218A	2	323700
20.8R34		TR218A	1	532649
9.5R36		TR218A	4	552918
13.6/14.9R36		TR218A	3	323621
11.2/12.4R38	290/90R38	TR218A	3	323631
13.6/15.5R38	380/80R38	TR218A	3	323720
16.9/18.4R38	480/80R38	TR218A	2	323690
20.8R38	520/85R38	TR218A	2	323710
18.4/20.8R42	480/520/80/85R42	TR218A	2	323740
16.9/18.4R46	480/80R46	TR218A	2	323693
320/90R50/54	NATURAL RUBBER	TR218A	1	557610



TR15CW Front tractor, L&G sizes. Valve is straight, rubber covered, 1.38" long. Maximum inflation is 60 psi. Rim hole 0.625". Not intended for use with liquid ballast. Not bendable.



TR218 Rear tractor, front tractor, flotation, forestry, L&G and drag racing sizes. Valve is 0.81" long and is designed to lock into rim hole using LN10 rim nut (supplied). Not bendable. Rim hole 0.625. Maximum inflation 150 psi. Made for liquid ballast.

TUBES

Severe Service Radial Tubes (Agricultural Use Only)

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
16.9/18.4R30	420/480/80/90R30	TR218A	1	550086
16.9/18.4R34	480/85R34	TR218A	1	550116
15.5R38		TR218A	1	550043
16.9/18.4R38	480/80R38	TR218A	1	550108
20.8R38	520/85R38	TR218A	1	550051
18.4R46	420/480/80R46	TR218A	2	323694

Forestry Radial Natural Rubber Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
38X1800NR20	42/48X2500NR20 3 3/4" OFF SET VALVE	TR218A	1	545236
16.9/18.4NR26		TR218A	1	534307
23.1NR26	650/750/55/65NR26.5	TR218A	1	533823
700/50NR26.5	600/55NR26.5	TR218A	1	550167
28LNR26		TR218A	1	533831
16.9/18.4NR30		TR218A	1	534315
24.5NR32		TR218A	1	542148
30.5LNR32	800/65R32	TR218A	1	533866
16.9/18.4NR34		TR218A	1	534323



Rear tractor, front tractor, flotation, forestry, L&G and drag racing sizes.
TR218 Valve is 0.81" long and is designed to lock into rim hole using LN10 rim nut (supplied). Not bendable. Rim hole 0.625. Maximum inflation 150 psi. Made for liquid ballast.

TUBES

Lawn & Garden, Trailer, Material Handling Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
280/250X4		TR87	10	320050
280/250X4		JS87P	10	320010
410/350X4		TR87	10	320100
410/350X4		TR13	10	320400
410/350X4	11X400X4	JS87P	10	320020
9X350X4		TR87	10	320030
340/300X5		TR87	10	320150
410/350X5		TR87	10	320200
410/350X5		TR13	10	320070
11X400X5		TR87	10	320080
410/350X6		TR87	10	320250
410/350X6		TR13	10	320160
11X600X5		TR87	10	323520
13X500X6	14X450X6	TR87	10	320260
13X500X6		TR13	10	323790
13X650X6		TR13	10	320170
530/450X6	145/70X6	TR87	10	320270
15X600X6		TR87	10	320290
15X600X6		TR13	10	323800
800X6/7		TR87	10	542962
300X8		TR13	10	320110
350/400X8		TR87	10	320360
350/400X8		TR13	10	320120
480/400X8		TR13	10	320400
570/500X8		TR13	10	320450
16X650/750X8		TR13	10	320420
18X850/950X8	20X800/1000X8, 22.5X10X8, 18X650/750X8	TR13	10	320410
690X9		TR13	10	321500
25X12X9, 25X13X9 RADIAL		TR6	10	321520
20X800/1000X10	21X800X10, 205/50X10	TR13	10	320770
480X12 / 530X12	5X12, 400X12	TR13	10	320901
6X12		TR13	10	322160
23/24X850/1050X12	22X750/950X12	TR13	10	321370
24X1200/1300X12	26X1050/1200X12	TR13	10	321050
24/25X850X14		TR13	10	322020



TR87 Industrial, mining, L&G sizes. Supplied bent on some sizes, straight on others. Straight length is 1.75", bent is 1.31". Maximum inflation is 150 psi. Rim hole 0.453". Not intended for use with liquid ballast.



TR13 Passenger, light truck, front tractor, industrial, L&G sizes. Valve is straight, rubber covered, 1.38" long. Maximum inflation is 60 psi. Rim hole 0.453". Not intended for use with liquid ballast. Not bendable. B6 bushing allows use in a 0.625" rim hole.



TR6 ATV sizes. Valve is straight metal stem that is 1.16" long. .305-32 threads and supplied with two hex nuts that go outside the rim. Rim hole .333". Max inflation 60 psi. Not intended for liquid ballast. Not bendable.

TUBES

ATV Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
145/70X6		TR87	10	320270
16X800X7		TR6	10	542970
RAD 20X7X8, 20X11X8, 22X12X8, 21X11X8, 20X7X9, 22X11X9		TR6	10	542997
RAD 21X11/12X8, 22X9/12X8, 20/22X7/8X9		TR6	10	320440
RAD 24X11X9, 25X12/13X9, 24X11X10, 25X11X10, 25X12X10		TR6	10	543004
RAD 25X12/13X9, 24X11X9, 25X11/12X10, 26X12X10		TR6	10	321520
RAD 18X10/11X10, 20X8/11X10, 22X8/11X10, 23X9/10X10		TR6	10	320771
RAD 18X11X10, 21X7X10, 22X9X10, 22X11X10, 23X7X10		TR6	10	543012
RAD 23X8X11, 23X8X12, 24X9X11, 25X8X12, 25X10X12		TR6	10	543020
RAD 24X12X12, 26/27X8X11, 26/27X8X12, 26X10/12X12		TR6	10	321051
RAD 25X12X12, 26X12X12, 26X9X12		TR6	10	557049

Forklift & Small Industrial Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
400X8, 480X8		JS2	12	322410
500X8, 570X8		JS2	36	323820
18X7X8		JS2	6	42915000
690/600X9		JS2	28	323830
21X8X9		TR75	6	42925000
650X10		JS2	22	323840
700X12		TR440	6	322420
825X15		TR442	12	323870
250X15		TR440	15	323880
28X12X15		TR440	10	323900

Radial Forklift & Small Industrial Tubes

Tube Size	Also Fits	Valve Stem	Carton Qty.	Stock Number
600R9, 690R9, 650R10		TR87	10	519405
700R12		TR440	10	533343
28X9R15, 29X8R15, 700R15, 815R15, 30X8R15		TR440	10	540625
32X12R15		TR440	10	552291
250/300R15		TR442	10	552216



TR87 Industrial, mining, L&G sizes. Supplied bent on some sizes, straight on others. Straight length is 1.75", bent is 1.31". Maximum inflation is 150 psi. Rim hole 0.453". Not intended for use with liquid ballast.



TR6 ATV sizes. Valve is straight metal stem that is 1.16" long. .305-32 threads and supplied with two hex nuts that go outside the rim. Rim hole .333". Max inflation 60 psi. Not intended for liquid ballast. Not bendable.



JS2 Industrial, trailer, L&G sizes. Supplied straight. Length 2.20". Maximum inflation is 60 psi. Rim hole 0.453". Not intended for use with liquid ballast.



TR75 Roller (compactor) sizes. Supplied bent. Bent length is 3.39". Maximum inflation is 150 psi. Rim should be slotted. Not intended for use with liquid ballast.



TR440 Light truck, truck-bus, mining sizes. Supplied bent. Bent length is 3.0 to 5.7 inches. Maximum inflation is 150 psi. Rim should be slotted. Not intended for use with liquid ballast.